

View Online at <https://aerobasegroup.com/nsn/5340-00-602-8644>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

0.954 inches

**Second Leg Length:**

1.253 inches

**Second Leg Width:**

3.888 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.120 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.260 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

2.423 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.375 inches

**First Leg Thickness:**

Between 0.116 inches and 0.132 inches

**Second Leg Thickness:**

Between 0.058 inches and 0.066 inches

**First Leg Width:**

3.888 inches

**First Leg Corner Radius:**

0.344 inches

**First Leg Distance Between Hole Centers Along Width:**

3.200 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.344 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.344 inches

**Second Leg End Radius:**

0.375 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0