

View Online at <https://aerobasegroup.com/nsn/5340-00-604-5907>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.130 inches and 1.260 inches

Second Leg Length:

Between 1.170 inches and 1.280 inches

Second Leg Width:

Between 0.500 inches and 0.520 inches

First Leg Slot Length:

Between 0.400 inches and 0.460 inches

First Leg Slot Width:

Between 0.220 inches and 0.240 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.290 inches and 0.350 inches

Second Leg Slot Length:

Between 0.380 inches and 0.420 inches

Second Leg Slot Width:

Between 0.280 inches and 0.300 inches

First Leg Thickness:

Between 0.058 inches and 0.068 inches

Second Leg Thickness:

Between 0.058 inches and 0.068 inches

First Leg Width:

Between 0.500 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.370 inches

First Leg End Radius:

Between 0.290 inches and 0.350 inches

Second Leg End Radius:

Between 0.290 inches and 0.350 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Ams 2485 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0