

View Online at <https://aerobasegroup.com/nsn/5340-00-609-3590>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.970 inches and 0.990 inches

Second Leg Length:

Between 1.497 inches and 1.548 inches

Second Leg Width:

Between 1.676 inches and 1.758 inches

Second Leg Corner Radius:

Between 0.297 inches and 0.328 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.082 inches and 1.102 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.297 inches and 0.328 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.340 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0