## NSN 5340-00-610-0919

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-610-0919 First Leg Length: 4.000 inches Second Leg Length: 5.000 inches Second Leg Width: 4.000 inches Second Leg End Width: 3.000 inches First Leg Slot Length: 2.188 inches First Leg Slot Width: Between 0.656 inches and 0.688 inches Second Leg Hole Diameter: 0.656 inches Second Leg Distance Between Upper Hole Centers Along Width: 2.250 inches Second Leg Distance Between Hole Centers Along Length: 1.875 inches Second Leg Distance Between First And Second Hole Centers Along Width: 1.125 inches Second Leg Distance From Edge To Hole Center Along Width: 0.875 inches **Second Leg Distance From Edge To Hole Center Along Length:** 1.250 inches First Leg Thickness: 0.375 inches Second Leg Thickness: 0.375 inches First Leg Width: 4.000 inches First Leg End Width: 3.000 inches First Leg Distance From Edge To Hole Center Along Width: 2.000 inches First Leg Distance From Edge To Hole Center Along Length: 1.516 inches First Leg Style: Square and tapered First Leg Hole Arrangement Style: One slot

Second Leg Style:

Square and tapered

## **NSN 5340-00-610-0919** Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Special Features:
Slot in second leg 1.312 in. Lg, 0.656 in. W
Material:
Steel
Material Specification:
Mil-s-13281 military specification single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-c-12968, type b, cl 1 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A042a0
Mil-std (military Standard):
Mil-s-13281 spec.