

View Online at <https://aerobasegroup.com/nsn/5340-00-610-0919>

First Leg Length:

4.000 inches

Second Leg Length:

5.000 inches

Second Leg Width:

4.000 inches

Second Leg End Width:

3.000 inches

First Leg Slot Length:

2.188 inches

First Leg Slot Width:

Between 0.656 inches and 0.688 inches

Second Leg Hole Diameter:

0.656 inches

Second Leg Distance Between Upper Hole Centers Along Width:

2.250 inches

Second Leg Distance Between Hole Centers Along Length:

1.875 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.875 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.250 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

4.000 inches

First Leg End Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.516 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Slot in second leg 1.312 in. Lg, 0.656 in. W

Material:

Steel

Material Specification:

Mil-s-13281 military specification single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-c-12968, type b, cl 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-13281 spec.