

View Online at <https://aerobasegroup.com/nsn/5340-00-611-0420>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.630 inches and 0.670 inches

**Second Leg Length:**

Between 1.105 inches and 1.145 inches

**Second Leg Width:**

Between 1.230 inches and 1.310 inches

**Second Leg Corner Radius:**

Between 0.230 inches and 0.270 inches

**First Leg Hole Diameter:**

Between 0.220 inches and 0.229 inches

**Second Leg Hole Diameter:**

Between 0.274 inches and 0.288 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.770 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg Thickness:**

Between 0.058 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.058 inches and 0.068 inches

**First Leg Width:**

0.770 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg End Radius:**

Between 0.230 inches and 0.270 inches

**First Leg Style:**

End radius and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Hole Arrangement Style:**

Two holes

**First Leg Angle:**

90.0 degrees

**Material:**

Nickel alloy

**Material Specification:**

Ams5599 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0