Angle Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-612-9374

| First Leg Length: |
|---|
| 0.900 inches |
| Second Leg Length: |
| 2.500 inches |
| Second Leg Width: |
| 2.000 inches |
| Second Leg End Width: |
| 0.470 inches |
| Second Leg Hole Diameter: |
| Between 0.200 inches and 0.206 inches |
| Second Leg Distance Between Hole Centers Along Width: |
| 0.680 inches |
| Second Leg Distance Between Hole Centers Along Length: |
| 1.670 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.770 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.500 inches |
| First Leg End Width: |
| 1.000 inches |
| First Leg Style: |
| Angle |
| Second Leg Style: |
| |
| Square and tapered |
| |
| Square and tapered |
| Square and tapered Second Leg Hole Arrangement Style: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-1-20 military standard single treatment response |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: N/a |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: N/a Unit Of Measure: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: N/a Unit Of Measure: Demilitarization: |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| Square and tapered Second Leg Hole Arrangement Style: Two holes First Leg Angle: 90.0 degrees Surface Treatment: Lacquer Surface Treatment Specification: Fed-std-595, tt-l-20 military standard single treatment response Style Designator: Angle Shelf Life: N/a Unit Of Measure: Demilitarization: |