

View Online at <https://aerobasegroup.com/nsn/5340-00-613-7295>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.735 inches and 0.765 inches

Second Leg Length:

Between 1.050 inches and 1.110 inches

Second Leg Width:

1.720 inches

Second Leg Corner Radius:

Between 0.230 inches and 0.270 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.228 inches

Second Leg Distance Between Hole Centers Along Width:

1.220 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Thickness:

Between 0.073 inches and 0.087 inches

Second Leg Thickness:

Between 0.073 inches and 0.087 inches

First Leg Width:

0.815 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.280 inches

First Leg End Radius:

Between 0.250 inches and 0.280 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0