

View Online at <https://aerobasegroup.com/nsn/5340-00-613-7301>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.860 inches and 0.910 inches

Second Leg Length:

Between 1.790 inches and 1.830 inches

Second Leg Width:

Between 2.318 inches and 2.358 inches

First Leg Hole Diameter:

0.344 inches

Second Leg Hole Diameter:

Between 0.418 inches and 0.428 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.360 inches and 0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.360 inches and 0.380 inches

First Leg Thickness:

Between 0.103 inches and 0.121 inches

Second Leg Thickness:

Between 0.103 inches and 0.121 inches

First Leg Width:

Between 1.845 inches and 1.895 inches

First Leg Corner Radius:

Between 0.300 inches and 0.320 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.245 inches and 1.255 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.300 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

Second Leg End Radius:

Between 0.360 inches and 0.380 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0