

View Online at <https://aerobasegroup.com/nsn/5340-00-614-0018>

Fabrication Method (non-core):

Machined

First Leg Length:

0.650 inches

Second Leg Length:

0.810 inches

Second Leg Width:

1.180 inches

First Leg Hole Diameter:

Between 0.170 inches and 0.176 inches

Second Leg Hole Diameter:

Between 0.144 inches and 0.150 inches

Second Leg Distance Between Hole Centers Along Width:

0.870 inches

Second Leg Distance Between Hole Centers Along Length:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.160 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

Center Section Height:

0.380 inches

Center Section Width:

1.180 inches

Center Section Thickness:

0.063 inches

First Leg Width:

1.180 inches

First Leg Distance Between Hole Centers Along Width:

0.812 inches

First Leg Distance From Edge To Hole Center Along Width:

0.180 inches

First Leg Distance From Edge To Hole Center Along Length:

0.180 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Mil-s-18729 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1 federal specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.