

View Online at <https://aerobasegroup.com/nsn/5340-00-616-5140>

Fabrication Method (non-core):

Stamped

First Leg Length:

1.190 inches

Second Leg Length:

1.750 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.279 inches and 0.288 inches

Second Leg Hole Diameter:

Between 0.217 inches and 0.225 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

Center Section Height:

0.280 inches

Center Section Width:

0.500 inches

Center Section Thickness:

Between 0.057 inches and 0.079 inches

First Leg Width:

0.500 inches

First Leg Corner Radius:

Between 0.057 inches and 0.079 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.380 inches

Second Leg End Radius:

0.380 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0