

View Online at <https://aerobasegroup.com/nsn/5340-00-616-5453>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.915 inches and 0.955 inches

Second Leg Length:

Between 1.290 inches and 1.330 inches

Second Leg Width:

Between 0.594 inches and 0.656 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.401 inches and 0.411 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg Thickness:

Between 0.058 inches and 0.066 inches

Second Leg Thickness:

Between 0.058 inches and 0.066 inches

First Leg Width:

Between 0.594 inches and 0.656 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg End Radius:

Between 0.406 inches and 0.469 inches

Second Leg End Radius:

Between 0.406 inches and 0.469 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0