NSN 5340-00-616-7199

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-616-7199

| Cross Sectional Shape: |
|---------------------------------------|
| Circular recess |
| Inside Diameter: |
| Between 4.047 inches and 4.079 inches |
| Hole Diameter: |
| Between 0.516 inches and 0.532 inches |
| Pilot Diameter: |
| Between 4.325 inches and 4.330 inches |
| Bolt Circle Diameter: |
| 5.250 inches |
| Flange Thickness: |
| 0.428 inches |
| Edge Shape: |
| Round, four ears and holes |
| Body Radius: |
| 4.875 inches |
| Inverted Radius: |
| 0.500 inches |
| Ear Radius: |
| 0.500 inches |
| Ear Quantity: |
| 4 |
| Bolt Circle Hole Quantity: |
| 4 |
| First Recess Inside Height: |
| 0.937 inches |
| Inside Corner Radius: |
| 0.250 inches |
| Body Thickness: |
| 0.188 inches |
| Outside Corner Radius: |
| 0.188 inches |
| Body Outside Radius: |
| 0.438 inches |
| Pilot Height: |
| Between 0.112 inches and 0.115 inches |
| Securing Device Type: |
| Special |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| Features Provided: |

Sealing capability

NSN 5340-00-616-7199

Access Cover - Page 2 of 2



| inside Angle: |
|--|
| 40.0 degrees |
| Special Features: |
| Mounting ears have boss 0.875 diax 0.063 h |
| Material: |
| Iron malleable |
| Surface Treatment: |
| Phosphate zinc |
| Fsc Application Data: |
| Mount howitzer, over 150mm through 200mm |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A531c0