

View Online at <https://aerobasegroup.com/nsn/5340-00-619-6668>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.210 inches and 1.250 inches

Second Leg Length:

Between 1.500 inches and 1.540 inches

Second Leg Width:

Between 0.594 inches and 0.656 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.199 inches and 0.209 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.310 inches and 0.330 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.594 inches and 0.656 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.310 inches and 0.330 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

Second Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A042a0