

View Online at <https://aerobasegroup.com/nsn/5340-00-622-7788>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.765 inches and 0.795 inches

Second Leg Length:

Between 1.160 inches and 1.200 inches

Second Leg Width:

Between 0.620 inches and 0.640 inches

First Leg Hole Diameter:

Between 0.199 inches and 0.209 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.310 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg Thickness:

Between 0.058 inches and 0.066 inches

Second Leg Thickness:

Between 0.058 inches and 0.066 inches

First Leg Width:

Between 1.040 inches and 1.090 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.245 inches and 0.255 inches

Second Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0