NSN 5340-00-624-0699

Angle Bracket - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5340-00-624-0699

| First Leg Length: 0.562 inches Second Leg Length: 1.688 inches Reinforcement Method (non-core): Web both sides Second Leg Width: 0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Slot Length: 0.438 inches Second Leg Slot Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.750 inches First Leg Distance From Edge To Hole Center Alon |
|--|
| Second Leg Length: 1.688 inches Reinforcement Method (non-core): Web both sides Second Leg Width: 0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Length: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches Second Leg Slot Width: 0.250 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches First Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Width: 0.750 inches |
| 1.688 inchesReinforcement Method (non-core):Web both sidesSecond Leg Width:0.750 inchesFirst Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.438 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesFirst Leg Thickness:0.051 inchesSecond Leg Thickness:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.750 inchesSinchesFirst Leg Distance From Edge To Hole Center Along Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.375 inches |
| Reinforcement Method (non-core):Web both sidesSecond Leg Width:0.750 inchesFirst Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.438 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.510 inchesFirst Leg Thickness:0.051 inchesSecond Leg Thickness:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.375 inches |
| Web both sidesSecond Leg Width:0.750 inchesFirst Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.438 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.510 inchesFirst Leg Thickness:0.051 inchesSecond Leg Width:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Width:0.750 inchesSinchesSecond Leg Slot Length:0.051 inchesSecond Leg Thickness:0.051 inchesSecond Leg Nickness:0.051 inchesSecond Leg Nidth:0.750 inchesSecond Leg NicknesSecond Leg Nick |
| Second Leg Width:0.750 inchesFirst Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.438 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesFirst Leg Thickness:0.051 inchesSecond Leg Nickness:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Width:0.750 inchesSitter Leg Width:0.750 inchesSitter Leg Nickness:0.750 inchesSitter Leg Nickness:0.750 inchesSitter Leg NicknesSitter Leg NicknesSitt |
| 0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Width: 0.750 inches |
| First Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.375 inchesSecond Leg Slot Length:0.438 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.250 inchesFirst Leg Thickness:0.051 inchesSecond Leg Width:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.750 inches |
| 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Width: 0.750 inches |
| First Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.438 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.250 inchesFirst Leg Thickness:0.051 inchesSecond Leg Thickness:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Width:0.375 inchesFirst Leg Width:0.375 inches |
| 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| Second Leg Distance From Edge To Hole Center Along Length: 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.438 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| Second Leg Slot Width: 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.250 inches First Leg Thickness: 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| First Leg Thickness:0.051 inchesSecond Leg Thickness:0.051 inchesFirst Leg Width:0.750 inchesFirst Leg Distance From Edge To Hole Center Along Width:0.375 inches |
| 0.051 inches Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| Second Leg Thickness: 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.051 inches First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| First Leg Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| First Leg Distance From Edge To Hole Center Along Width: 0.375 inches |
| 0.375 inches |
| |
| First Lag Distance From Edge To Hele Conter Along Length |
| This Ley Distance From Edge TO Hole Center Along Length: |
| 0.312 inches |
| First Leg End Radius: |
| 0.500 inches |
| Second Leg End Radius: |
| 0.500 inches |
| First Leg Style: |
| End radius |
| First Leg Hole Arrangement Style: |
| One slot |
| |
| Second Leg Style: |
| Second Leg Style: End radius |
| |

NSN 5340-00-624-0699

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t4 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0