

View Online at <https://aerobasegroup.com/nsn/5340-00-626-1563>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.740 inches and 0.820 inches

Second Leg Length:

Between 0.960 inches and 1.000 inches

Second Leg Width:

Between 1.660 inches and 1.720 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.344 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.180 inches and 1.200 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.570 inches and 0.590 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.300 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.360 inches and 0.400 inches

First Leg End Radius:

Between 0.360 inches and 0.400 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0