

View Online at <https://aerobasegroup.com/nsn/5340-00-628-5034>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.620 inches and 0.660 inches

Second Leg Length:

Between 0.840 inches and 0.880 inches

Second Leg Width:

Between 2.480 inches and 2.560 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.280 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.280 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.280 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 2.480 inches and 2.560 inches

First Leg Corner Radius:

Between 0.240 inches and 0.280 inches

First Leg Distance Between Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.460 inches and 0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0