

View Online at <https://aerobasegroup.com/nsn/5340-00-631-1213>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.484 inches and 0.516 inches

Second Leg Length:

Between 0.484 inches and 0.516 inches

Reinforcement Method (non-core):

Raised center center section

Second Leg Width:

Between 0.969 inches and 1.031 inches

First Leg Hole Diameter:

Between 0.184 inches and 0.186 inches

Second Leg Hole Diameter:

Between 0.196 inches and 0.201 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.609 inches and 0.641 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.172 inches and 0.204 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.156 inches and 0.172 inches

First Leg Thickness:

Between 0.086 inches and 0.094 inches

Second Leg Thickness:

Between 0.086 inches and 0.094 inches

Center Section Height:

Between 0.328 inches and 0.360 inches

Center Section Width:

Between 0.969 inches and 1.031 inches

Center Section Thickness:

Between 0.086 inches and 0.094 inches

First Leg Width:

Between 0.969 inches and 1.031 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.422 inches and 0.454 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.265 inches and 0.297 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.172 inches and 0.204 inches

First Leg Style:

Extended flat

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

120.0 degrees

Second Leg Angle:

120.0 degrees

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0