NSN 5340-00-631-1213

Double Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-00-631-1213



Fabrication Method (non-core): Stamped First Leg Length: Between 0.484 inches and 0.516 inches Second Leg Length: Between 0.484 inches and 0.516 inches **Reinforcement Method (non-core):** Raised center center section Second Leg Width: Between 0.969 inches and 1.031 inches First Leg Hole Diameter: Between 0.184 inches and 0.186 inches Second Leg Hole Diameter: Between 0.196 inches and 0.201 inches Second Leg Distance Between Hole Centers Along Width: Between 0.609 inches and 0.641 inches Second Leg Distance From Edge To Hole Center Along Width: Between 0.172 inches and 0.204 inches Second Leg Distance From Edge To Hole Center Along Length: Between 0.156 inches and 0.172 inches First Leg Thickness: Between 0.086 inches and 0.094 inches Second Leg Thickness: Between 0.086 inches and 0.094 inches **Center Section Height:** Between 0.328 inches and 0.360 inches **Center Section Width:** Between 0.969 inches and 1.031 inches **Center Section Thickness:** Between 0.086 inches and 0.094 inches First Leg Width: Between 0.969 inches and 1.031 inches First Leg Distance Between Hole Centers Along Width: Between 0.422 inches and 0.454 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.265 inches and 0.297 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.172 inches and 0.204 inches First Leg Style: Extended flat First Leg Hole Arrangement Style: Two holes

NSN 5340-00-631-1213

Double Angle Bracket - Page 2 of 2



Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
120.0 degrees
Second Leg Angle:
120.0 degrees
Heat Treatment:
H-32 strain hardened
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8, h32 federal specification single material response
Surface Treatment:
Chromate
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0