

View Online at <https://aerobasegroup.com/nsn/5340-00-631-3075>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.415 inches and 1.555 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.455 inches and 0.525 inches

Second Leg Slot Length:

Between 0.710 inches and 0.730 inches

Second Leg Slot Width:

Between 0.213 inches and 0.223 inches

First Leg Thickness:

Between 0.115 inches and 0.135 inches

Second Leg Thickness:

Between 0.115 inches and 0.135 inches

Center Section Width:

Between 1.620 inches and 1.700 inches

Center Section Thickness:

Between 0.115 inches and 0.135 inches

First Leg Width:

Between 2.010 inches and 2.090 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.300 inches and 1.320 inches

First Leg Distance Between Upper Hole Centers Along Width:

Between 1.300 inches and 1.320 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.190 inches and 0.370 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.280 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One slot

First Leg Angle:

90.0 degrees

Second Leg Angle:

135.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0