

View Online at <https://aerobasegroup.com/nsn/5340-00-631-3075>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 1.415 inches and 1.555 inches

**First Leg Hole Diameter:**

0.281 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.455 inches and 0.525 inches

**Second Leg Slot Length:**

Between 0.710 inches and 0.730 inches

**Second Leg Slot Width:**

Between 0.213 inches and 0.223 inches

**First Leg Thickness:**

Between 0.115 inches and 0.135 inches

**Second Leg Thickness:**

Between 0.115 inches and 0.135 inches

**Center Section Width:**

Between 1.620 inches and 1.700 inches

**Center Section Thickness:**

Between 0.115 inches and 0.135 inches

**First Leg Width:**

Between 2.010 inches and 2.090 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 1.300 inches and 1.320 inches

**First Leg Distance Between Upper Hole Centers Along Width:**

Between 1.300 inches and 1.320 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.190 inches and 0.370 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.280 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One slot

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

135.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0