

View Online at <https://aerobasegroup.com/nsn/5340-00-631-3099>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.780 inches and 0.830 inches

Second Leg Length:

Between 0.990 inches and 1.050 inches

Second Leg Width:

Between 2.140 inches and 2.180 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

1.660 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.085 inches and 0.101 inches

Second Leg Thickness:

Between 0.085 inches and 0.101 inches

Center Section Height:

Between 1.155 inches and 1.191 inches

Center Section Thickness:

Between 0.085 inches and 0.101 inches

First Leg Width:

Between 2.320 inches and 2.360 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

1.840 inches

First Leg Distance Between Hole Centers Along Length:

0.040 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.160 inches and 0.170 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

107.0 degrees

Second Leg Angle:

107.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0