NSN 5340-00-632-6606

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-632-6606

First Leg Length:

Between 0.469 inches and 0.531 inches

Second Leg Length:

Between 1.719 inches and 1.781 inches

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

Between 0.196 inches and 0.201 inches

Second Leg Hole Diameter:

Between 0.281 inches and 0.290 inches

Second Leg Distance Between Hole Centers Along Width:

0.750 inches

Second Leg Distance Between Hole Centers Along Length:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Thickness:

Between 0.059 inches and 0.067 inches

Second Leg Thickness:

Between 0.059 inches and 0.067 inches

First Leg Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.219 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-00-632-6606 Angle Bracket - Page 2 of 2



Heat Treatment:
H-32 strain hardened
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:
Angle
Fsc Application Data:
Controls missile guidance set
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.