

View Online at <https://aerobasegroup.com/nsn/5340-00-632-7205>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

0.761 inches

**Second Leg Length:**

1.437 inches

**Second Leg Width:**

2.100 inches

**Second Leg Corner Radius:**

0.312 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.480 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.340 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

Between 0.074 inches and 0.082 inches

**Second Leg Thickness:**

Between 0.074 inches and 0.082 inches

**First Leg Width:**

2.487 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.652 inches

**First Leg Distance Between Hole Centers Along Length:**

0.029 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Offset Angle:**

83.5 degrees

**Material:**

Steel comp 4130 or steel comp 8630

**Material Specification:**

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0