

View Online at <https://aerobasegroup.com/nsn/5340-00-632-7206>

Fabrication Method (non-core):

Machined

First Leg Length:

0.875 inches

Second Leg Length:

1.284 inches

Second Leg Width:

2.120 inches

Second Leg Corner Radius:

0.312 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance Between Hole Centers Along Width:

1.480 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.280 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

Between 0.074 inches and 0.082 inches

Second Leg Thickness:

Between 0.074 inches and 0.082 inches

First Leg Width:

2.120 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

1.105 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

103.5 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0