

View Online at <https://aerobasegroup.com/nsn/5340-00-633-7959>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.910 inches and 0.940 inches

Second Leg Length:

Between 3.004 inches and 3.056 inches

Second Leg Width:

Between 1.490 inches and 1.510 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Distance Between Hole Centers Along Length:

Between 2.160 inches and 2.200 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.320 inches and 0.370 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 1.689 inches and 1.749 inches

First Leg Corner Radius:

Between 0.300 inches and 0.330 inches

First Leg Distance Between Hole Centers Along Width:

1.089 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.300 inches and 0.330 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.330 inches

Second Leg End Radius:

Between 0.234 inches and 0.266 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0