NSN 5340-00-649-6858

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-649-6858 First Leg Length: 0.562 inches Second Leg Length: 1.500 inches Second Leg Width: 1.609 mils and 1.641 centimeters **Second Leg Corner Radius:** Between 0.109 inches and 0.141 inches First Leg Slot Length: 0.437 inches First Leg Slot Width: 0.125 inches Second Leg Hole Diameter: 0.144 mils and 0.149 centimeters Second Leg Distance Between Hole Centers Along Width: 2.375 inches Second Leg Distance Between Hole Centers Along Length: 0.750 inches Second Leg Distance From Edge To Hole Center Along Width: 0.187 inches Second Leg Distance From Edge To Hole Center Along Length: 0.250 inches First Leg Thickness: Between 0.045 inches and 0.055 inches Second Leg Thickness: Between 0.045 inches and 0.055 inches First Leg Width: 1.625 inches First Leg Corner Radius: 0.125 inches First Leg Distance From Edge To Hole Center Along Length: 0.313 inches First Leg Style: Corner radius First Leg Hole Arrangement Style: One slot Second Leg Style: Corner radius **Second Leg Hole Arrangement Style:** Four holes

Not identical

Second Leg Relationship To First Leg:

NSN 5340-00-649-6858 Angle Bracket - Page 2 of 2



| First Leg Angle: |
|---|
| 90.0 degrees |
| Special Features: |
| First leg has two slotted holes equally spaced, second leg has rectangle hole in center |
| Material: |
| Aluminum alloy 5052 |
| Material Specification: |
| Qq-a-250/8, h32 federal specification single material response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |