# NSN 5340-00-655-7978

Rigid Caster - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-655-7978

# Center To Center Distance Between Bolt Holes Along Width:

Between 0.995 inches and 1.005 inches

# Center To Center Distance Between Bolt Holes Along Length:

Between 2.295 inches and 3.005 inches

# Wheel Quantity:

1

# Safe Operating Load Rating:

100.0 pounds

## Material And Location:

Steel, aisi c1010 plate err-100 err-100 or steel, aisi c1020 plate err-100 err-100 or steel, qq-s-633, comp c1010-canceled plate err-100 err-100 or steel, qq-s-633, comp c1020-canceled plate err-100 err-100

## Surface Treatment And Location:

Lacquer plate err-100 err-100

# Wheel Type:

Built up

## Wheel Diameter:

2.000 inches

## **Effective Height:**

3.000 inches

#### **Plate Style:**

Rectangular

#### Wheel Bearing Type:

Plain, self-lubricated

# Tread Width:

1.000 inches

#### Caster Plate Length:

3.875 inches

# Caster Plate Width:

1.500 inches

#### **Caster Plate Mounting Hole Diameter:**

0.332 inches

#### **Special Features:**

Laguna blue

#### Style Designator:

Rigid

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A25600