

View Online at <https://aerobasegroup.com/nsn/5340-00-658-7156>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.860 inches and 0.900 inches

Second Leg Length:

Between 1.413 inches and 1.453 inches

Second Leg Width:

Between 1.835 inches and 1.915 inches

Second Leg Corner Radius:

Between 0.230 inches and 0.270 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.219 inches

Second Leg Distance Between Hole Centers Along Width:

1.375 inches

Second Leg Distance Between Hole Centers Along Length:

0.593 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Thickness:

Between 0.082 inches and 0.098 inches

Second Leg Thickness:

Between 0.082 inches and 0.098 inches

First Leg Width:

Between 1.421 inches and 1.429 inches

First Leg Corner Radius:

Between 0.230 inches and 0.270 inches

First Leg Distance Between Hole Centers Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0