# NSN 5340-00-663-1344

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-663-1344

## Center To Center Distance Between Bolt Holes Along Width:

4.875 inches

#### Center To Center Distance Between Bolt Holes Along Length:

6.750 inches

## Wheel Quantity:

2

Tire Size:

4.00-8

### Safe Operating Load Rating:

1200.0 pounds

#### Material And Location:

Rubber tire err-100 err-100

#### Surface Treatment And Location:

Aluminum alloy wheel rim err-100 err-100

## Unpackaged Unit Weight:

74.000 pounds

## Wheel Type:

Pneumatic tire

### Wheel Diameter:

8.000 inches

Effective Height:

20.000 inches

## **Features Provided:**

Brake lock and shock absorber and swivel lock

**Plate Style:** 

Rectangular

#### Wheel Bearing Type:

Roller

### Swivel Bearing Type:

Annular ball

#### **Swivel Bearing Arrangement:**

One row

## King Bolt Bearing Type:

Roller

#### **Tread Width:**

4.000 inches

#### **Caster Plate Length:**

8.250 inches

## **Caster Plate Width:**

6.250 inches

#### **Caster Plate Mounting Hole Diameter:**

0.625 inches

# NSN 5340-00-663-1344

Swivel Caster - Page 2 of 2

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A25600

