

View Online at <https://aerobasegroup.com/nsn/5340-00-663-1495>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

1.375 inches

**Second Leg Length:**

1.625 inches

**Second Leg Width:**

1.625 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.245 inches and 0.260 inches

**Second Leg Hole Diameter:**

Between 0.280 inches and 0.290 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.896 inches and 0.916 inches

**Second Leg Distance Between Hole Centers Along Length:**

Between 1.105 inches and 1.125 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

Between 0.062 inches and 0.063 inches

**Second Leg Thickness:**

Between 0.062 inches and 0.063 inches

**First Leg Width:**

1.375 inches

**First Leg Corner Radius:**

0.125 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.063 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Hole Arrangement Style:**

Two holes

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 8630

**Material Specification:**

Mil-std-66 military standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 1 federal specification single treatment response

**Style Designator:**

Angle

**Fsc Application Data:**

Bracket, angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-std-66 spec.