

View Online at <https://aerobasegroup.com/nsn/5340-00-663-1495>

Fabrication Method (non-core):

Machined

First Leg Length:

1.375 inches

Second Leg Length:

1.625 inches

Second Leg Width:

1.625 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.245 inches and 0.260 inches

Second Leg Hole Diameter:

Between 0.280 inches and 0.290 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.896 inches and 0.916 inches

Second Leg Distance Between Hole Centers Along Length:

Between 1.105 inches and 1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.062 inches and 0.063 inches

Second Leg Thickness:

Between 0.062 inches and 0.063 inches

First Leg Width:

1.375 inches

First Leg Corner Radius:

0.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

1.063 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Material:

Steel comp 8630

Material Specification:

Mil-std-66 military standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 1 federal specification single treatment response

Style Designator:

Angle

Fsc Application Data:

Bracket, angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-66 spec.