

View Online at <https://aerobasegroup.com/nsn/5340-00-663-2986>

Fabrication Method (non-core):

Machined

First Leg Length:

0.860 inches

Second Leg Length:

1.320 inches

Second Leg Width:

0.600 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.343 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.300 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.010 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

Between 0.590 inches and 0.610 inches

First Leg Distance From Edge To Hole Center Along Width:

0.300 inches

First Leg Distance From Edge To Hole Center Along Length:

0.415 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

Second Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.047 degrees and 0.078 degrees

Material:

Steel comp 8630

Material Specification:

Fed-std-66 federal standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0