

View Online at <https://aerobasegroup.com/nsn/5340-00-663-9409>

First Leg Length:

Between 1.265 inches and 1.355 inches

Second Leg Length:

Between 1.670 inches and 1.730 inches

First Leg Hole Diameter:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.395 inches and 0.425 inches

Second Leg Slot Length:

Between 0.490 inches and 0.510 inches

Second Leg Slot Width:

Between 0.250 inches and 0.270 inches

First Leg Thickness:

0.064 inches

Second Leg Thickness:

0.064 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.250 inches and 1.260 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.375 inches and 0.385 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.310 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-4 solution heat treated

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.