

View Online at <https://aerobasegroup.com/nsn/5340-00-663-9409>

**First Leg Length:**

Between 1.265 inches and 1.355 inches

**Second Leg Length:**

Between 1.670 inches and 1.730 inches

**First Leg Hole Diameter:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.395 inches and 0.425 inches

**Second Leg Slot Length:**

Between 0.490 inches and 0.510 inches

**Second Leg Slot Width:**

Between 0.250 inches and 0.270 inches

**First Leg Thickness:**

0.064 inches

**Second Leg Thickness:**

0.064 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 1.250 inches and 1.260 inches

**First Leg Distance Between Hole Centers Along Length:**

Between 0.375 inches and 0.385 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.250 inches and 0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.250 inches and 0.310 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Heat Treatment:**

T-4 solution heat treated

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.