

View Online at <https://aerobasegroup.com/nsn/5340-00-664-1349>

Wheel Quantity:

1

Safe Operating Load Rating:

Not rated

Stem Style:

Plain round

Stem Length:

Any acceptable

Stem Diameter:

Any acceptable

Material And Location:

Steel body

Surface Treatment And Location:

Nickel body

Wheel Type:

Built up

Wheel Diameter:

Between 1.625 inches and 1.750 inches

Effective Height:

Any acceptable

Stem Socket Style:

Tubular

Wheel Bearing Type:

Plain, self-lubricated

Swivel Bearing Type:

Ball

Swivel Bearing Arrangement:

One row or two row

Tread Width:

0.719 inches

Stem Socket Depth:

0.906 inches

Stem Socket Diameter:

0.437 inches

Special Features:

Nonstaining, nonmarking cushion treads, permanently bonded, impact resistant, hard rubber composition core; wheels tread thickness 3/16in.; wheel tread and core material hardness range hard rubber 55-75 shore d, soft rubber 55-70 shore a; tensile 1500 psi min., adhesion between tread and core is 50 lbs per inch of width; axles and stems - cold drawn steel, nut and bolt combination or solid rivet type and permanently fastened; ball bearings - corrosion resistant, case hardened ground steel; assembly with a water repellent grease

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A25600