

View Online at <https://aerobasegroup.com/nsn/5340-00-680-3588>

**Fabrication Method (non-core):**

Forged

**First Leg Length:**

1.000 inches

**Second Leg Length:**

0.875 inches

**Second Leg Width:**

0.500 inches

**First Leg Hole Diameter:**

Between 0.217 inches and 0.225 inches

**Second Leg Hole Diameter:**

Between 0.279 inches and 0.288 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

Between 0.062 inches and 0.063 inches

**Second Leg Thickness:**

Between 0.062 inches and 0.063 inches

**First Leg Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg End Radius:**

0.375 inches

**Second Leg End Radius:**

0.375 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1010

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Fsc Application Data:**

Engine, turb prop turbo-jet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0