## NSN 5340-00-680-4613

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-680-4613

First Leg Length:

Between 0.860 inches and 0.900 inches

Second Leg Length:

Between 0.980 inches and 1.020 inches

Second Leg Width:

Between 0.740 inches and 0.760 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.365 inches and 0.385 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.240 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.740 inches and 0.760 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.365 inches and 0.385 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.370 inches and 0.390 inches

First Leg End Radius:

Between 0.484 inches and 0.516 inches

Second Leg End Radius:

Between 0.484 inches and 0.516 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

## NSN 5340-00-680-4613

Angle Bracket - Page 2 of 2



| Material S | Specif | icat | ion |  |
|------------|--------|------|-----|--|
|------------|--------|------|-----|--|

Ams 5504 assn standard single material response

**Style Designator:** 

Angle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A042a0