

View Online at <https://aerobasegroup.com/nsn/5340-00-684-9996>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Countersunk

First Leg Length:

0.469 inches

Second Leg Length:

0.563 inches

Second Leg Width:

Between 0.365 inches and 0.415 inches

First Leg Hole Diameter:

Between 0.185 inches and 0.187 inches

Second Leg Hole Diameter:

Between 0.062 inches and 0.064 inches

Second Leg Distance Between Hole Centers Along Length:

Between 0.154 inches and 0.158 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.094 inches

First Leg Thickness:

0.051 inches

Second Leg Thickness:

0.051 inches

First Leg Width:

Between 0.365 inches and 0.415 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg End Radius:

0.188 inches

Second Leg End Radius:

0.094 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy

Surface Treatment:

Anodize

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0