

View Online at <https://aerobasegroup.com/nsn/5340-00-685-0479>

First Leg Length:

1.000 inches

Second Leg Length:

0.590 inches

Second Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg End Radius:

Between 0.360 inches and 0.400 inches

Second Leg End Radius:

Between 0.360 inches and 0.400 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

Annealed

Material:

Steel comp 302

Material Specification:

Mil-s-5059 military specification single material response

Surface Treatment:

Passivate

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.