

View Online at <https://aerobasegroup.com/nsn/5340-00-685-1159>

Mounting Hole Type:

Counterbored

First Leg Length:

0.870 inches

Second Leg Length:

4.130 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.217 inches and 0.255 inches

Second Leg Hole Diameter:

Between 0.279 inches and 0.288 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.052 inches and 0.068 inches

Second Leg Thickness:

Between 0.058 inches and 0.068 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Heat treatment: quenched and tempered

Material:

Steel comp 4130

Material Specification:

Mil-s-18729 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.