## NSN 5340-00-689-6218

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-689-6218

| Fabrication Method (non-core):                             |
|--|
| ,  |
| Stamped  First Log Longth                                  |
| First Leg Length: 1.500 inches                             |
|  |
| Second Leg Length:   |
| 1.500 inches   |
| Second Leg Width:  |
| 3.500 inches   |
| Second Leg End Width:                                      |
| 3.047 inches   |
| Second Leg Hole Diameter:                                  |
| Between 0.280 inches and 0.287 inches                      |
| Second Leg Distance Between Hole Centers Along Width:      |
| 2.590 inches   |
| Second Leg Distance From Edge To Hole Center Along Width:  |
| 0.440 inches   |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.810 inches   |
| First Leg Thickness:                                       |
| 0.196 inches   |
| Second Leg Thickness:                                      |
| 0.196 inches   |
| First Leg Width:   |
| 3.500 inches   |
| First Leg Style:   |
| Square   |
| First Leg Hole Arrangement Style:                          |
| No hole  |
| Second Leg Style:  |
| Square and tapered   |
| Second Leg Hole Arrangement Style:                         |
| Two holes  |
| Second Leg Relationship To First Leg:                      |
| Not identical  |
| First Leg Angle:   |
| 90.0 degrees   |
| Special Features:  |
| Second leg tapered 7 to 9 degrees both ends                |
| Heat Treatment:  |
| T-4 solution heat treated                                  |
| Material:  |

Aluminum alloy 2024

## NSN 5340-00-689-6218

Angle Bracket - Page 2 of 2



Qq-a-200/3 federal specification single material response or qq-a-200/13 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-std-171, fn 7.2.1 or 7.3.1 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.