NSN 5340-00-691-0143

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-691-0143 First Leg Length: 1.080 inches Second Leg Length: 1.170 inches Second Leg Width: 3.500 inches **Second Leg Corner Radius:** 0.400 inches First Leg Hole Diameter: Between 0.339 inches and 0.349 inches Second Leg Hole Diameter: Between 0.276 inches and 0.286 inches Second Leg Distance Between Hole Centers Along Width: 0.250 inches Second Leg Distance Between Hole Centers Along Length: 2.700 inches Second Leg Distance From Edge To Hole Center Along Width: 0.400 inches Second Leg Distance From Edge To Hole Center Along Length: 0.400 inches First Leg Thickness: Between 0.087 inches and 0.101 inches Second Leg Thickness: Between 0.087 inches and 0.101 inches First Leg Width: 3.500 inches First Leg Corner Radius: 0.310 inches First Leg Distance Between First And Second Hole Centers Along Width: 0.959 inches First Leg Distance Between Second And Third Hole Centers Along Width: 0.959 inches First Leg Distance From Edge To Hole Center Along Width: 0.312 inches First Leg Distance From Edge To Hole Center Along Length: 0.310 inches First Leg Style: Corner radius First Leg Hole Arrangement Style: Three holes

Second Leg Style:

Corner radius

NSN 5340-00-691-0143 Angle Bracket - Page 2 of 2



| Second Leg Hole Arrangement Style: |
|--|
| Two holes |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 97.0 degrees |
| Special Features: |
| One additional mtg hole in first leg |
| Material: |
| Steel comp 4130 or steel comp 8630 |
| Material Specification: |
| Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| A-5 2400 assn standard single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A042a0 |
| |
| |