

View Online at <https://aerobasegroup.com/nsn/5340-00-691-0149>

Fabrication Method (non-core):

Stamped

First Leg Length:

1.740 inches

Second Leg Length:

4.250 inches

Second Leg Width:

1.570 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance Between Hole Centers Along Width:

0.300 inches

Second Leg Distance Between Hole Centers Along Length:

3.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.600 inches

First Leg Thickness:

Between 0.087 inches and 0.101 inches

Second Leg Thickness:

Between 0.087 inches and 0.101 inches

First Leg Width:

1.580 inches

First Leg Corner Radius:

0.310 inches

First Leg Distance Between Hole Centers Along Width:

0.300 inches

First Leg Distance Between Hole Centers Along Length:

3.400 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0