

View Online at <https://aerobasegroup.com/nsn/5340-00-695-6914>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

1.070 inches rod connection and 1.110 inches rod connection

**Shank Length:**

Between 1.480 inches and 1.520 inches

**Hole Diameter:**

Between 0.312 inches and 0.313 inches

**Shank Diameter:**

0.438 inches

**Overall Height:**

Between 1.240 inches and 1.260 inches

**Overall Width:**

Between 0.695 inches and 0.705 inches

**End Radius:**

Between 0.620 inches and 0.630 inches

**Fork Span Width:**

Between 0.435 inches and 0.445 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 2.730 inches and 2.770 inches

**Fork Arm Thickness:**

0.120 mils and 0.130 centimeters

**Fork Depth:**

Between 1.000 inches and 1.140 inches

**Thread Size:**

0.438 inches rod connection

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-500, cond f military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ps362, the boeing co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-500 spec.