

View Online at <https://aerobasegroup.com/nsn/5340-00-700-0122>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.611 inches and 0.671 inches

Second Leg Length:

Between 0.768 inches and 0.881 inches

Second Leg Width:

Between 2.507 inches and 2.570 inches

Second Leg Corner Radius:

Between 0.281 inches and 0.344 inches

First Leg Hole Diameter:

Between 0.198 inches and 0.208 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

2.226 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.281 inches and 0.344 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

First Leg Thickness:

Between 0.057 inches and 0.067 inches

Second Leg Thickness:

Between 0.057 inches and 0.067 inches

Center Section Height:

Between 1.107 inches and 1.137 inches

Center Section Width:

0.500 inches

Center Section Thickness:

Between 0.057 inches and 0.067 inches

First Leg Width:

Between 0.560 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.280 inches and 0.320 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0