

View Online at <https://aerobasegroup.com/nsn/5340-00-703-1430>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.154 inches rod connection

Shank Length:

1.279 inches

Hole Diameter:

Between 0.312 inches and 0.313 inches

Shank Diameter:

0.344 inches

Overall Height:

1.250 inches

Overall Width:

Between 1.190 inches and 1.200 inches

End Radius:

Between 0.563 inches and 0.813 inches

Fork Span Width:

Between 0.814 inches and 0.824 inches

Securing Pin Hole Diameter:

0.093 inches

Distance From Center Of Securing Pin Hole To Rod End:

0.529 inches

Distance From Pivot Pinhole Center To Rod Connection End:

5.625 inches

Fork Arm Thickness:

0.188 inches

Fork Depth:

Between 1.031 inches and 1.062 inches

Shank Shoulder Diameter:

Between 0.873 inches and 0.874 inches

Shank Shoulder Length:

3.096 inches

Thread Size:

0.625 inches rod connection

Material:

Steel comp 4340

Material Specification:

Fed standard 66 federal standard single material response or aoso/sae assn standard single material response

Surface Treatment:

Cadmium body and chromium body

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response body and qq-c-320 federal specification single treatment response body

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0