## **NSN 5340-00-720-6446**Rigid Caster - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-00-720-6446 |
|---|
| Center To Center Distance Between Bolt Holes Along Width:     |
| Between 3.360 inches and 3.390 inches                         |
| Center To Center Distance Between Bolt Holes Along Length:    |
| Between 5.235 inches and 5.265 inches                         |
| Wheel Quantity:   |
| 1   |
| Tire Size:  |
| 8.250   |
| Safe Operating Load Rating:                                   |
| 350.0 pounds  |
| Material And Location:  |
| Rubber tire err-100 err-100                                   |
| Surface Treatment And Location:                               |
| Anodized plate err-100 err-100                                |
| Unpackaged Unit Weight:                                       |
| 8.600 pounds  |
| Wheel Type:   |
| Semipneumatic tire  |
| Wheel Diameter:   |
| 8.600 inches  |
| Effective Height:   |
| 10.100 inches   |
| Features Provided:  |
| Brake lock  |
| Plate Style:  |
| Rectangular   |
| Wheel Bearing Type:   |
| Tapered roller  |
| Disassembly Capability:                                       |
| Provided  |
| Tread Width:  |
| 2.540 inches  |
| Caster Plate Length:  |
| 6.500 inches  |
| Caster Plate Width:   |
| 4.620 inches  |
| Caster Plate Mounting Hole Diameter:                          |
| Between 0.520 inches and 0.545 inches                         |
| Style Designator:   |
| Rigid   |

Shelf Life: N/a

## **NSN 5340-00-720-6446**Rigid Caster - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

Demilitarization:

No

Fiig:

A25600