

View Online at <https://aerobasegroup.com/nsn/5340-00-720-8073>

Center To Center Distance Between Bolt Holes Along Width:

Between 3.355 inches and 3.395 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 5.230 inches and 5.270 inches

Wheel Quantity:

1

Safe Operating Load Rating:

560.0 pounds

Material And Location:

Rubber, soft tread

Surface Treatment And Location:

Any acceptable

Unpackaged Unit Weight:

30.000 pounds

Wheel Type:

Built up

Wheel Diameter:

8.000 inches

Effective Height:

Between 10.156 inches and 10.344 inches

Features Provided:

Axle lubrication fitting and swivel lock and swivel lubrication fitting and electrically conductive

Plate Style:

Rectangular

Wheel Bearing Type:

Ball or roller

Swivel Bearing Type:

Ball or roller

Swivel Bearing Arrangement:

One row

Tread Width:

2.500 inches

Caster Plate Length:

7.312 inches

Caster Plate Width:

5.438 inches

Caster Plate Mounting Hole Diameter:

Between 0.521 inches and 0.541 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600